

# 550TVL

High Speed Dome Camera

# IR PIONEER

Germany OSRAM Infrared Overlay and Finland LEDIL Optical Technology


## IPTZIR36XWDRDNSNH2

150m IR Distance



## Features

- 150m IR distance, multiple IR Mode(Off ,far ,near and all on)
- Pan speed 0.1--300°/s ,Tilt speed 0.1--200°/s
- English OSD menu, menu password protection
- 220 preset positions
- 4 Auto scan modes, 4 Tours(each 27 presets), 4 pattern tracks(each 180 seconds)
- Privacy zone function
- RS485, Pelco D, P protocol auto detect
- High quality motor provides stable and low noise performance
- Leisure action setup
- Pan/tilt position and zoom times displayable
- Clock and temperature info displayable
- Aluminum alloy vandal proof housing
- Compatible zoom with Sony, Samsung, Hitachi, LG, CNB
- Fan and heater inside, Low temperature Protection IP66 waterproof
- 5500V lightning proof capability, AC24V power input



# IR PIONEER

## IPTZIR36XWDRDNSNH2

Germany OSRAM Infrared Overlay and Finland LEDIL Optical Technology



### Specification

<b>Model</b>	<b>IPTZIR36XWDRDNSNH2</b>
<b>Operation</b>	
Zoom Lens	Sony 36X zoom, D/N 1/4" sony ExViewHAD (color :530TVL,B/W:570TVL), f=3.4-122.4mm (F1.6-4.5), Color:0.07Lux B/W:0.01Lux IR-CUT WDR
OSD menu	English, password protection
Preset position	220
IR LED	14 wing high-power infrared lamp
IR-LED distance	150m
IR-LED Mode	off,near ,far ,On
Scan	Auto scan and left-right limited scan, speed adjustable
Patrol	4 tracks, 27preset per track, speed and dwell time changeable
Pattern	4 tracks, 180s for each
Alarm	N/A
Private masking	Supported function based on zoom module
Address range	0--255
Communication	RS485
Baud rate	2400/4800/9600/19200, setup by dip switcher
Protocol	Pelco-P/D auto detected, or others customized
Leisure action	Home place/Scan/Patrol/Pattern
Device title	Display on/off
P/T position	Display on/off
Zoom times	Display on/off
Temperature info	Display on/off
<b>Mechanical</b>	
Pan range	0°~ 360° continuously
Pan speed	0.1~ 300°/s
Tilt range	0°~ 93° auto flip on/off performance
Tilt speed	0.1~ 200°/s
Precision	0.1°
<b>Others</b>	
Housing	Aluminum alloy, vandal proof housing
Lighting proof	With 5500V video, data and power lighting proof
Water proof	IP66
Work temp	-40°C~ 60°C
Work humidity	Max 95%
Power	AC24V
Installation	Outdoor and indoor installation
Package size	228*166*365mm
Package weight	5kg

### Multi-function

#### 14EA LED Array and 150 Meters IR Distance



#### 8 Privacy Mask Zone



#### 5500V lighting proof capability



Introducing the Germany OSRAM brand LED, providing a better image quality and with lower power consumption

Insert heat treatment device to reduce the cavity temperature of the PTZ dome and to prevent the fog inside of the dome

